Irradiation chamber BS-02





The irradiation chamber BS-02 is compact, robust equipment for the time- or dose-controlled irradiation of samples with UV radiation. The chamber can be fully equipped for one of the spectral regions UV-C, UV-B or UV-A to achieve the highest irradiance. Alternately, the use of two separately controlled lamp groups for different spectral regions allows for especially flexible operation of the chamber. With interchangeable lamps, the BS-02 is really flexible. No tools are required for lamp replacement.

The interior irradiation chamber has a base area of 46 x 32 cm² and a height of 23 cm. The sample chamber operating temperature is about 25° C - 30° C so that thermal damage to the specimen is avoided. Due to the high uniformity of the irradiation, the samples may be positioned in any order.

For the BS-02 we offer two irradiation controllers, the UV-MAT and the UV-MAT Touch. Both irradiation controllers can control two spectral ranges separately and achieves a consistent dose regardless of lamp aging, contamination or temperature. The dose is measured with calibrated sensors. For this purpose, the sensor already contains an extremely precise analog-digital converter and a temperature sensor.



compact dimensions

Large and secured front door

The memory in the sensor contains all sensor identifications and the calibration history.

The UV-MAT Touch also records the irradiations and can be controlled by the PC. This makes multi-stage irradiations and the documentation of the irradiation possible.

Applications:

- Irradiation of bacteria and cell cultures
- Photostability testing
- UV and daylight material testing
- Post-treatment for rapid prototyping / 3D printing
- UV curing, sealing, and bonding
- UVC aging and disinfection

TECHNICAL DATA BS-02

Interior chamber	46 x 32 x 23 cm
Dimensions	58 x 40 x 47 cm
Weight	~ 32 kg
Power consumption	180 W
Mains	110 - 230 V _{AC} , 50/60 Hz
Operation temperature	10 to 40 °C
Humidity	< 80% non-condensing
Lamp lifetime UVC	up to 9.000 h
Lamp lifetime UVB	up to 4.000 h
Lamp lifetime UVA	up to 4.000 h
Number of lamps	8
Sample temperature	25 °C +/- 5°C
Irradiance UVA	8 mW/cm ²
Irradiance UVA Actinic	8 mW/cm ²
Irradiance UVB	5 mW/cm ²
Irradiance UVC	10 mW/cm ²
Sample temperature	The cooling uses ambient air
	typically the temperaure of
	the samples is ambient + 5 °C

Listed irradiance values are max values.

TECHNICAL DATA UV-MAT

Sensor connectors	24 bit, fully digital
Number of sensors	2
Dose range	0 - 1.000.000 J/cm ²
Dose resolution	1 mJ/cm ²
AD conversion	24 bit
PC interface	USB 2.0
Sensor identification	yes
Dimensions	185 mm x 251 mm x 100 mm
Operation temperature	5 - 60 °C
Spectral ranges	
UVC	200 - 280 nm
UVB	280 - 315 nm
UVA	315 - 400 nm



Calibration uncertainty	4,5 - 7,0% (k=2)
Linearity error	< 1%
Aging / year	< 3%

Opsytec Dr. Gröbel GmbH Am Hardtwald 6-8, 76275 Ettlingen, Germany







With interchangeable lamps, the BS-02 is extremely flexible. For the lamp replacement no tools are required.

Our calibrations are available as factory and ISO 17025 calibrations and are traceable to PTB standards.

hone +49 - 7243 - 94 783 - 50 ax +49 - 7243 - 94 783 - 65

www.opsytec.com info@opsytec.com certified according DIN EN ISO 9001:2015

i

i

OPSYTEC PRODUCT INFORMATION

UV-MAT TOUCH

The UV-MAT Touch user interface is a high-resolution capacitive touchscreen. A powerful Cortex ARM processor ensures durability and updateability. This means that new functions can be installed directly on site. The UV-MAT Touch and the PC software are Windows 10 /11 compatible.

Numerical and graphical single and multi-channel irradiations, oscillograms and the settings are clearly displayed. The parameterization is done intuitively directly on the UV-MAT Touch and is password protected.

TECHNICAL DATA UV-MAT TOUCH

Display	Capacitive touch display
	5" WVGA
Display output	Irradiance + dose
	Oscilloscope view
Data recording rate	adjustable: 1 s - 1 h
Recording duration	> 24000 h
Memory interface	1 USB flash drive (up to 32 GB)

Irradiation Lamp group 2 - UVB Lamp group 1 - UVA Q Q 100 % 100 % UVA 0,12 mW/cm² 4,36 mW/cm² D_{is} 1,16 J/cm² D_{is} D_{set} 100.0 J/cm² Deat 100,0 J/cm² O0:00:00.00.00 [dd : hh :mm : ss] 00 Х 6 18.07.2022

TECHNICAL DATA UV-MAT

Display	graphical, 128 x 64 px
	monochrom
Display output	Irradiance + dose
	-
Data export	via USB
Recording duration	-

FEATURES IN DETAIL

The differences are:

Did you know? The UV-MAT and the UV-MAT Touch use the same sensors. Therefore, these can be used on both devices.



	UV-MAT Touch	UV-MAT
Display	Capacitive touch display	monochrom, 128 x 64 px
Memory	USB flash drive	-
Number of channels	2	2
Irradiance, dose and temperature measurement	\checkmark	\checkmark
Time and dose controlled irradiations	\checkmark	\checkmark
Recordings of measurements	\checkmark	-
Oscilloscope view	\checkmark	-
Screenshots can be saved on USB flash drive	\checkmark	-
Pause and restart of irradiations	\checkmark	-
Add notes and comments to the irradiation	\checkmark	-
Remote control from PC	\checkmark	-
Irradiation logs	USB flash drive	PC
User control & admin mode	\checkmark	-
Easy firmware upgrades	✓	\checkmark

Phone +49 - 7243 - 94 783 - 50 Fax +49 - 7243 - 94 783 - 65

certified according DIN EN ISO 9001:2015

INCLUDED ACCESSORIES

The irradiation chamber is modular expandable and thus optimal for different applications.

The following functions are always included:

DOSE CONTROLLER



The irradiation controller UV-MAT continuously measures the irradiance and stops the irradiation at the set target dose.



The dose control UV-MAT Touch offers alternatively all functions of the UV-MAT, but simplifies the operation and documentation of the irradiations.

SENSORS

Calibrated radiometric sensors are available for each



spectral range. The integrated diffuser ensures the required cosine correction. Excellent long-term stability is achieved through the use of appropriate materials. The

sensors are calibrated with traceability to PTB (the German national test authority); after being calibrated, they are supplied with a factory calibration certificate.

SENSOR HOLDER

The sensor holder fixates one or two radiometer sensors laterally in the irradiance chamber. The sensors are removable for the measurement of the irradiance on the material to be irradiated. That way, the irradiance can be determined at the desired location. Via a factor, the UV-MAT can be adjusted.

CONTROL AND DIMMING



Two lamp groups can be controlled and dimmed separately.

Example: 4 UVA and 4 UVB lamps.

The lamps are dimmable. The irradiance can be reduced to approx. 30%.

LAMPS



We offer the right lamps for different applications. With interchangeable lamps, the BS-02 is extremely flexible. Examples:

UVA-352 is used for the UV aging

process with indoor applications and UVB lamps for the acceleraded outdoor applications. UVC is used for the UV disinfection.

TIMER



Alternative to the dose control, we offer a settable timer. This timer is suitable for a simple irradiation between 0,01 s and 9999 h. Timer is included in the standard system.

IRRADIATION LOGS



The irradiations can be recorded with a PC.

The UV-MAT Touch also records irradiations on a USB flash drive without a PC.

Opsytec Dr. Gröbel GmbH Am Hardtwald 6-8, 76275 Ettlingen, Germany

Phone +49 - 7243 - 94 783 - 50 Fax +49 - 7243 - 94 783 - 65

www.opsytec.com info@opsytec.com

OPTIONAL ACCESSORIES

The following functions are optionally available:

ATTENUATOR



Attenuators each reduce the irradiance to approx. 30%. We offer area attenuators and lamp attenuators. Both attenuators reduce the irradiance to 30% each. Use e.g. for the irradiation of cell cultures.

INERT GAS BOX



Working under inert-conditions is possible with our removeable inert gas boxes.

Separate gas inlets and outlets allow the measurement of O2

concentration at gas outlet. Available with top window made of high quality glass for UVA / VIS irradiations or UV fused silica for UVB and UVC irradiations.

PC SOFTWARE FOR UV-MAT TOUCH

Complex, multi-stage irradiations, e.g. a pre-irradiation with UV-A at low irradiance and then a high-intensity UV-C irradiation can be easily and individually parameterized with the remote control option. Up to 30 doseor time-controlled steps and pauses are possible.

At the same time the irradiation is logged and stored on the PC.

PC connection: USB 2.0



OPTIONS

All irradiation chambers can be equipped with different options.

For example, for cell or virus irradiation and other laboratory applications, the dose control UV-MAT Touch and attenuators are often used to achieve an extremely uniform and reproducible irradiation.

Medical applications benefit from the irradiation documentation, which is automatically controlled remotely.

We would be pleased to support you with your individual configuration of an irradiation chamber.

PART NUMBERS

BS-02	860902
UV-MAT Touch	820930
UV-MAT	820920
PC-Software UV-MAT TOUCH	860901
Radiometric sensors	8144XX
ISO 17025 calibration	17025
Lamps / spare lamps	8608XX
Inert box UVA or UVC	86802-iA / -iC
Attentuator for lamps	870000
Area Attentuator	870001

Our calibrations are available as factory and ISO 17025 calibrations and are traceable to PTB standards. IP65 sensors, further measuring and spectral ranges available. Just ask us!

Opsytec Dr. Gröbel GmbH Am Hardtwald 6-8, 76275 Ettlingen, Germany Phone +49 - 7243 - 94 783 - 50 fax +49 - 7243 - 94 783 - 65

www.opsytec.com nfo@opsytec.com